

CRYO-ZET

Air Cooling System

Designed to enhance patient comfort and treatment outcomes after procedures. With its powerful cooling capabilities (up to -31°F) and compatibility with various laser types, the Cryo-Zet ensures effective pain reduction while minimizing recovery time.

Compatible with

Smixel, Shiny Plus, Pico Premium, Q10 Premium

Controls
Heat
Exposure

Enhances
Patient's
Comfort

Reduce
Post-treatment
Discomfort



Key Advantages:

- Maintains cooling air temperature (Max. -31°F)
- Rapid cooling facilitated by a high-quality compressor
- Automatic adjustable control system
- Auto-detecting mechanism to maintain optimal conditions

Specification

A.C Input	220V, 50/60Hz
Air level	10 Step
Dimension	400 mm (W) x 540 mm (L) x 940 mm (H)
Air flow output	1000L/Min
Temperature	0 ~ -35°C
Weight	50 kg

Smart accessories that elevate comfort, safety, and results. Contact us today!

DS-3000E

Smoke Evacuator

The next-generation aerosol and smoke evacuator, engineered to minimize airborne contamination during laser treatments. Its advanced triple-stage filtration system, combined with UV LED sterilization, provides exceptional air purification. A built-in noise silencer ensures quiet operation, while the lightweight, free-moving arm offers ergonomic flexibility and mobility in clinical settings.

Compatible with

Smaxel, Pico Premium, Q10 Premium, Smartrion Combi



Key Advantages:

- Triple Filtration Power: Dust + Carbon + HEPA/ULPA Filter (99.9% efficiency)
- UV & LED Sterilization: Effectively eliminates bacteria and viruses.
- Ergonomic Design: Lightweight 3-joint free arm, foot-switch activation, and medical-grade casters for easy positioning and mobility.
- Adjustable Suction & Speed Control: Allows precise airflow and suction settings based on procedural needs.
- Quiet Operation: Noise silencer ensures a calm and comfortable treatment environment.

Specification

Power supply	Single phase AC 200V-240V /50-60Hz 100V-130V , 50-60Hz
Output power	1200W (120V), 1200W(230V)
Air flow	3.9m/ 3 min
Air pressure	3.0Kpa(Ø40) / 10Kpa(Ø25) / 22.5Kpa(Ø10)
Control mode	step 0~9 (10 steps)
Filters	1st filter (Dust filter) 2nd filter (Ulpa/Hepa filter) 3rd filter (Carbon filter)
Noise level	approx.49~65dB
Arm size	1,600mm
Arm weight	1.2 kg
Dimension	300 mm (W) x 320 mm (D) x 710 mm (H)
Weight	20 kg

